Modification Of Some Physical-Chemical Features of the Soil Following the Application of Municipal Sludge

Stefan BAKOS¹, Marilena MARGHITAS^{2*}

¹ Soil and Agrochemical Studies Office Cluj, Fagului Street no. 1, Cluj-Napoca, Romania;

² University of Agricultural Sciences and Veterinary Medicine Cluj-Napoca, 3-5, Mănăştur Street, 400372, Cluj-Napoca, Romania;

* corresponding author: *mmarghitas@usamvcluj.ro*

Bulletin USAMV series Agriculture 71(2)/2014

Print ISSN 1843-5246; Electronic ISSN 1843-5386

DOI 10.15835/buasvmcn-agr: 10285

Abstract

The use of municipal sludge in agriculture on a longer period leads inevitably to changing of some physical, chemical and biological soil properties. The amount of sludge that can be administered is subjected to a number of factors like: land orography, morphological, chemical and physical soil properties, but the decisive factor is the heavy metal content in the soil and sludge amount to be applied. Thus it was found that after a period of four years, the application of an amount of 230 t sludge/ha resulted in a decrease of 13% in clay fraction, which decreased by 4% the bulk density and a field capacity increase by 2%. At the same time changes were observed in terms of attributes and chemical composition of the soil: pH increases by 0.7 units, humus content increase by 7%, nitrogen 30%, phosphorus by 228%, 2% potassium and the largest increase was recorded in heavy metal content of the soil compared to the control. Cd concentration increased by 92%, Cu 123%, Cr 94%, Ni 31%, 143% Zn, Hg 100% and the highest increase was recorded in the Pb content, respectively 154%.

Keywords: *municipal sludge, heavy metals, pollution.*

INTRODUCTION

The amount of sludge resulting from wastewater treatment plants is increasing from year to year therefore it is necessary to find solutions to neutralize their ecological and economical properties.

Application of municipal sludge in agriculture is an effective method of recycling organic waste from tailings stations (Calciu and Dumitru, 2005).

Sludge dosage that can be administered and its value as a fertilizer, is diminished by the presence of pollutants and heavy metals (Schmidt, 1997; Henning et al., 2001), thereby influencing both quantitative and especially qualitative agricultural production. In order to be applied on agricultural lands, sludge must meet certain conditions: must not be a source of infection with pathogens, pollutants content must not exceed the maximum limits (Schmidt, 1997).

Besides these considerations it is necessary to apply the most appropriate technology - choosing a suitable soil dosage and timing of application to meet crop rotation (Mihalache et al., 2006).

Also, long-term use of municipal sludge in agriculture as a fertilizer, inevitably leads to the accumulation of heavy metals in the soil but also in biomass over the limits (Chambers, 2002), being one of the biggest risks of pollution in the agricultural practice.

Prevention of exceeding the maximum permissible concentrations requires periodic monitoring of the soil and sludge used (Korentear, 1991; Dumitru et al., 1993; Chambers, 2012).

This study has as main goal the tracking of physical and chemical soil properties following the application of sewage sludge on a mollic aluviosol, for a period of four years.

MATERIALS AND METHODS

The proposed plot of land for the application of sludge from the treatment plant Cluj-Napoca is located in the physical-geographical corridor of Small Somes, its floodplain terrace, at a distance of about 1600 m of the built area of Cluj-Napoca, near the tramway depot.

From the pedological point of view the soil is a specific one identified as river meadow, mollic aluviosol, pedologically following the next formula: Am 0-31cm, A/C – 31-52 cm, Ck₁ 52 -83 cm, Ck₂ 83-120 cm. It presents a glomerular structure in the first horizon, sub-angular polyhedral in the horizon A / C and is unstructured in Ck₁ and Ck₂.

Following the evolution of physico-chemical indicators was conducted over a period of four years, the application of 230 t/ha/year of sludge from the wastewater treatment plant Cluj-Napoca. Physico-chemical properties were determined before and after the application of sludge from three sampling points at a depth of 30 cm, while the determination of heavy metals was made to the material from the decanting station. Soil texture was determined by the method Kacinski, total nitrogen - Kjeldahl, mobile phosphorus and potassium - colormetric, pH - potentiometric,

humus - Walklez-Black, coefficient of hygroscopic - Mitscherlich, total porosity, wilting coefficient and field capacity by calculation, heavy metals - the disintegration wet-mix of strong acids, followed by determination using the atomic absorption spectrometry with the spectrophotometer Perkin Elmer Elan DRC II.

RESULTS AND DISCUSSIONS

In determining the suitability of land for for the application of sludge arising from the treatment plant from the unincorporated area of Cluj-Napoca, we took into account soil suitability criteria for evaluating the application of sewage sludge as required by law.

These criteria include both elements of the terrain orography and some physical and chemical features of the ground. Thus, the factors that determine the suitability of land for sewage sludge application are: terrain topography, slope, soil texture, permeability, global drainage, threat of erosion, water usable capacity, groundwater depth, edaphic useful volume, soil pH, cation exchange capacity and and not least the heavy metal content of the soil .

Tab. 1. Specific physical and hydro properties

Horizon	Harvesting depth -cm-	Size analysis					DA g/cm ³	PT %	Hydrophysical indices			
		Rough sand	Fine sand	Dust I	Dust II	Clay			CH	CO	CC	CU
Am	0-30	11.5	37.5	12.2	10.0	30.3	1.35	50	6.0	9.0	20	11
Am	0-30	10.5	34.4	10.0	10.4	34.7	1.26	53	8.6	12.9	23	10.1
Am	0-30	9.3	41.3	7.3	9.0	33.4	1.32	51	8.5	12.75	23	10.25

Note: DA –bulk density, PT – total porosity, CH – coefficient of hygroscopicity, CO – wilting coefficient, CC – field capacity, CU – usable water capacity.

Tab. 2. Chemical properties and heavy metal content of soil before application of sewage sludge

Horizon	Harvesting depth -cm-	pH	Humus %	N total %	P mobile ppm	K mobile ppm	Heavy metals mg/kg						
							Cd	Cu	Cr	Ni	Pb	Zn	Hg
Am	0-30	6.91	4.01	0.136	21	187	0.13	20	8.10	20	21	105	0.10
Am	0-30	6.93	3.86	0.143	20	188	0.12	21	8.16	21	19	101	0.10
Am	0-30	6.96	3.98	0.158	17	161	0.13	17	8.11	17	26	102	0.12

Tab. 3. Heavy metal content of sewage sludge treatment originated from the plant from Cluj-Napoca

Indicator	Value mg/kg	Maximum permitted quantity mg/kg
Cadmiu (Cd)	0.29	10
Cupru (Cu)	33	500
Crom (Cr)	32.8	500
Nichel (Ni)	6.2	100
Plumb (Pb)	35	300
Zinc (Zn)	131	2000
Mercur (Hg)	0.19	5

Tab. 4. The suitability of sewage sludge on land application

Nr crt	Factor	Extent of damage				Excluded
		without	weak	medium	high	
1	Land topography	very weak uneven	-	-	-	-
2	Land slope	< 2%	-	-	-	-
3	Soil texture		medium loamy clay	-	-	-
4	Soil permeability		high		-	-
5	Global soil drainage	-	-	-	intensive drainage	-
6	Risk of erosion	absent	-	-	-	-
7	Useful water capacity		medium	-	-	-
8	Groundwater depth	-	-	medium		-
9	Useful edaphic volume	-			medium	-
10	pH	>6.9				-
11	Cation exchange capacity	-	high	-	-	-
12	Heavy metal load	-	20-40%	-	-	-

Physical and hydro properties of the soil before applying sludge are shown in Table 1.

In Table 2 are shown the chemical characterization of soil elements: pH, content of humus, nitrogen, phosphorus, potassium, and heavy metal content of sludge before application.

From the table above follows that the soil on which is to be administered sludge, does not contain heavy metals above the maximum limit allowed: 3 mg/kg Cd, 100 mg/kg Cu, 100 mg/kg Cr, 50 mg/kg Ni, 50 mg/kg Pb, 300 mg/kg Zn and 1 mg/kg Hg.

In order to determine the amount of sludge needed and the determination of heavy metal content:

In table 4 are presented the limiting factors that determine the suitability of the land taken in the study of sludge application. As observed, the edaphic medium volume and high permeability of soil are elements that have a fairly high degree of restriction, but do not exclude the land from the management station from materials from decantation.

After applying the sludge over a period of four years, at a dose of 230 t/ha/year and incorporating it into the soil by deep plowing, first changes were observed in terms of argillaceous fraction size analysis. Thus the percentage of clay (under 0.002 mm fraction) decreased on average by 13%, due to sandy texture of sludge applied. This lowers the

Tab. 5. Modification of some physical and hydro indicators of soil after applying sewage sludge

Horizon	Harvesting depth -cm-	Granulometric analysis					DA g/cm ³	PT %	Hydro-physical indices			
		Coarse sand	Finely sand	Dust I	Dust II	Clay			CH	CO	CC	CU
Am	0-30	19.87	39.56	5.96	9.69	24.91	1.30	52	7.2	10.8	24	13.2
Am	0-30	11.78	40.49	4.90	8.93	27.90	1.21	55	9.7	14.5	25	10.5
Am	0-30	4.54	35.69	9.74	17.08	32.95	1.29	52	9.4	14.1	26	11.9

Tab. 6. Modification of some chemical properties of the soil after applying sewage sludge

Horizon	Harvesting depth -cm-	pH	Humus %	N total %	P mobile ppm	K mobile Ppm
Am	0-30	7.76	4.13	0.196	56	191
Increase compared to the control %		-	2.99	44	166	2
Am	0-30	7.88	4.31	0.174	71	189
Increase compared to the control %		-	11.65	20	255	0.5
Am	0-30	7.92	4.17	0.198	62	167
Increase compared to the control %		-	4.77	25	264	3.7

apparent density by 4%, while increasing pore space between soil particles. In addition sludge fertilization leads to increase of soil porosity in the case of the field studied by 3.9%, and the modification of hydro indices, especially field capacity by 2% and usable water capacity by 13% (Table 5).

Regarding changes on humus and potassium content increases are modest: 7 and 2%, but substantially the changes were observed in phosphorus, where growth has exceeded 220%. In addition pH has a significant increase by 0.7 units. Basically limed sludge had the role of an amendment.

The most significant changes were recorded however in the increase of heavy metal content in soil. The concentration of Cadmium (Cd) recorded an increase of 92%, Copper (Cu) 123% Chromium (Cr) 94%, Nickel (Ni) 31%, Zinc (Zn) by 143%, Mercury (Hg) by 100% and the largest increase was recorded for Lead (Pb) of 154%. None of these elements however exceeded the maximum load allowed (Fig. 1, 2, 3).

CONCLUSION

Application of sewage sludge produced after a relatively short period changes both regarding physical and hydro properties of soil as well as its chemical composition.

Thus, after a period of four years, the application of an amount of 230 t/ha/ year on a mollic aluviosol resulted in decreased clay fraction, decreased bulk density, followed by increasing of soil porosity. Among the hydro-physical indicators showed a modest increase the field capacity and usable water capacity.

More profound are the changes of chemical nature: the pH increased significantly, similar to the effect of applying limestone amendments. This was because the sludge from the treatment plant was treated with lime. The content of humus and microelements underwent modest changes, except for phosphorus.

Fertilization with sewage sludge however resulted in a substantial accumulation of heavy metals, with increases ranging between 31% and 154%, but without being exceeded the maximum admissible level. In order not to exceed the

Fig. 1. Sludge fertilization effects: the increase of the cadmium and copper

Fig. 2. Sludge fertilization effects: increased content of chromium and nickel

Fig. 3. Sludge fertilization effects: the increase of lead and zinc

maximum permissible values is very important that in addition to the analysis of pollutants of sludge and soil where it is to be applied, to be given importance for the measurement of soil suitability, given its physicochemical properties and orographic factors of the land.

REFERENCES

1. Calciu I., Dumitru E., (2000). The use of compost made from municipal sludge. Proceedings of the XVI National Conference of Soil Science, vol III, Suceava.
2. Chambers B., (2011). The impact on soil and plants of heavy metals in sludge, researching the sludge directive – A conference on Sewage Sludge.
3. Dumitru M., Rauta C., (1993). Influence of municipal sludge on soil and agricultural production. Annals ICPA, Vol. II, p.285-293.
4. Henning B.J., Snyman H.G., Aveling T.A.S. (2001). Plant soil interactions of sludge-borne heavy metals and the effect on maize, Water SA 27(1):71-78.
5. Korentejar L., (1991). A review of the agricultural use of sewage sludge: benefits and hazards, Water SA 17(3): 189-196.
6. Mihalache M., Dumitru M., Raducu D., Gament E., (2006). Harnessing municipal sludge in agriculture, Publishing House Solness, Timisoara.
7. Schmidt J.P., (1997). Understanding phytotoxicity threshold for trace elements in land-applied sewage sludge, J. Environ. Qual. 26:4-10.